



Summer Specials

Valid from Jul. 1, 2014 to Sep. 30, 2014

Prices Subject to Change Without Notice & Stock Availability.

HOT PRICES ON ALL MITUTOYO ITEMS WHILE QUANTITIES LAST!



Digimatic Calipers - Series 500

Featuring Absolute Linear Encoder technology and large .295" high LCD digits. While Quantities Last.

Model No.	Measuring Range	LCD Resolution	A.C.T. No.	Price \$				
500-196-30	0-6" (0-150mm)	.0005" (0.01mm)	282331	127.97				
500-197-30	0-8" (0-200mm)	.0005" (0.01mm)	284648	183.02				
500-193	0-12" (0-300mm)	.0005" (0.01mm)	114610	345.22				
500-506-10	0-24" (0-310mm)	.0005" (0.01mm)	36007	766.32				
With SPC C	utput			SPC				
Model No. Measuring Range		LCD Resolution	A.C.T. No.	Price \$				
500-171-20	0-6" (0-150mm)	.0005" (0.01mm)	105152	160.70				



Coolant Proof Digimatic Calipers

Features digital display as well as protection against dust and water spray from any direction. The world's first coolantproof caliper!

Model No.	Measuring Range	LCD Resolution	A.C.T. No.	Price \$	
500-752-10	0-6" (0-150mm)	.0005" (0.01mm)	187346	165.17	
500-754-10	0-12" (0-300mm)	.0005" (0.01mm)	175012	321.41	



Dial Calipers - Series 505

- · Resolution: .001"
- · Extra-rigid main beam
- · Sliding surfaces of the main blade are coated with titanium

Model No.	Measuring Range	Range/ Rev	Accuracy	A.C.T. No.	Price \$
505-675	0-6"	.10"	± .001"	187329	110.11
505-676	0-8"	.10"	± .001"	173258	152.52









Tubular Inside Micrometer - Series 137 \$450.12

Model No. 137-214

A.C.T. No. 35491

• Range: 2-40"

• Extension Rods: .5", 1", 2", 4" (2pcs), 6", 8", 12"

Mitutoyo



Inside Micrometers - Series 141

Model No. 141-233

A.C.T. No. 35511

\$171.12

Popular measuring instrument due to ease of use and wide range of measuring capacity.

• Range: 2-12"

Spacing Collar: .500"Rod Diameter: .248"

Mitutoyo



Outside Micrometers - Series 103

The 103 Series is the workhorse of micrometers. Carbide faces, Ratchet Stop for exact repetitive readings. Includes standards.

Model No.	Range	Graduation	A.C.T. No.	Price \$
103-177	0-1"	.001"	35279	67.70
103-178	1-2"	.001"	35280	78.12

Mitutoyo



Outside Micrometers

Model No. 104-138

\$509.64

A.C.T. No. 35349

- Wide measuring range with interchangeable anvils
- Carbide-tipped spindle
- Provided with Ratchet Stop for constant force
- Range: 6-12"

• Includes: 6 Anvils & 6 Standards



Dial Indicators - Series 2

Model No. 2416S

A.C.T. No. 64780

\$83.33

Group 2 Dial Indicators feature Inch – ANSI Standard stem (3/8") with lug back. Regular dial Indicator shown.

Range: 1"Grad: .001"

• Dial Reading: 0-100

Mitutoyo



"Quick Set" Test Indicators - Series 513

Direct gear train design means a higher level of sensitivity and reliability. Features jeweled bearings and standard dovetail mount. Complete unit includes: 2 contact points (.039" & .118"), 2 mounting stems with nut (3/8" & 5/32"),1 square arm and 1 swivel clamp.

Horizontal Type

Model No.	Unit	Grad.	Range	Dial Reading	Accuracy	A.C.T. No.	Price \$
513-402	Basic Unit	.0005"	.03"	0-15-0	± .0005"	109739	88.54
513-402T	Complete Unit	.0005"	.03"	0-15-0	± .0005"	107938	127.97

Pocket Test Indicator Set

Model No. 513-518T

A.C.T. No. 150400

\$130.94

Jeweled bearings assure higher sensitivity and accuracy. Complete set including accessories and carrying case.

Grad.: .001"Range: .04"

Dial Reading: 0-20-0Accuracy: ±.0002"



Dial Indicator and Magnetic Stand Set \$153.26 Model No. 7046PCK A.C.T. No. 151702

Moulded custom case with indicator: 1" range, .001" graduation and 0-100 dial reading. Mag base with 132 lbs. pull. Great value!

Dial Indicator: 2416FMagnetic Stand: 7010SN



Magnetic Stand

Model No. 7010SN

\$69.19

A.C.T. No. 116918

Mitutoyo Magnetic Stands accept all AGD-type Dial Indicators, Test Indicators and Probes having 3/8" Dia. shank and/or Lug Back with 1/4" Dia. mounting hole. ON-OFF Switch offers instant mounting.

· Includes: 6" rod and universal clamp

• Magnetic Pull: 132 lbf



Universal Magnetic Stand

Model No. 7033B

\$169.63

A.C.T. No. 264275

- This magnetic stand is a device that enables the setting of dial indicators and dial test indicators in any position
- Fine adjustment mechanism allows easy instrument zeroing
- Can be used with instruments with stem diameter: Ø8mm, Ø6mm, Ø9.525mm

• Magnetic Pull: 134 lbf



Telescoping Gages - Series 155 \$172.61

Model No. 155-903

A.C.T. No. 35549

• Range: .313"-6"

No. of Gages: 6-gage set



Thread Pitch Gauges - Series 188

Model No.	Range	Description	Order No.	Price \$
188-111	4 - 42 TPI	Unified Screw Pitch Gages 60° (30 leaves)	35701	27.53
188-151	4 - 42 & 0.4-7mm	TPI Unified 60° (30 leaves) & Metric 60° (21 leaves)	35704	52.82

Mitutoyo





Mitutoyo



Pocket Steel Rule - Series 950

Model No. 950-300

A.C.T. No. 64411

Size: 6" x 150 mm

Graduations: 1 mm, 1/64"

• Width: 1/2"

Mitutoyo



Steel Rules - Series 182

Satin chrome finish and stainless tempered. Engraved on front side only. Backside has Inch/Metric equivalents.

Model No.	Size		Grad	Graduations		Width	A.C.T. No.	Price \$
182-105	6" x 150mm	1/32	1/64	1mm	2mm	3/4"	35587	12.65
182-122	12" (16R)	1/32	1/64	1/50	1/100th	1"	35593	26.04

Mitutoyo




Edge Finder

Mitutoyo edge finders are hardened and ground on all surfaces.

Model No.	Shank Dia.	Tip Dia.	A.C.T. No.	Price \$
050101	3/8" (.375")	.20"	58042	20.83
050102	1/2" (.5")	.20"	58043	21.58

Mitutoyo



Combination Square Sets - Series 180 \$233.61 Model No. 180-905B A.C.T. No. 281928

Combination Square sets are available in a large variety of styles and sizes.

Set Type: InchLength: 12"

Blade Model: (4R) 180-501U
Square Head Model: 180-102U
Centre Head Model: 180-202U*
Protractor Head Model: 180-301U
*Hardened Cast Iron Centre Head



Permanent Magnetic Lifters

- Lift and transfer Steel & Iron without slings, hooks or cables and avoiding damage to the surface finish
- 3.5x safety coefficient & no power required, eliminates hazards due to power failures, no running costs

Dimensions & Weight

Model	Contact	Surface			Wainb.	A.C.T. No.	
No.	W	L	Н	L	Weight	A.C.I. NO.	
MLQ-100	2.44"	3.62"	2.63"	6.50"	6.60 lbs	264903	
MLQ-300	3.62"	6.37"	3.58"	8.30"	22 lbs	259653	
MLQ-600	4.80"	9.13"	4.60"	11.90"	52.8 lbs	264904	
MLQ-1000	6.90"	10.15"	6.41"	16.30"	110 lbs	264905	
MLQ-2000	9.21"	14.88"	8.34"	22.70"	275 lbs	264906	
MLQ-3000	11.26"	18.03"	10.28"	27.88"	484 lbs	264908	



Capacities

oup												
		Steel Plate			Ro	und Steel	(Not Hollo	ow)	Maximum			
Model No.	Max. Lifting Capacity		Min. Thickness Required			Max. Lifting Capacity		Max. Diameter		Length		Price \$
	lbs	kg	In	mm	lbs	kg	In	mm	In	mm		
MLQ-100	220	100	0.59"	15	99	45	5.9"	150	39"	1000	264903	330.40
MLQ-300	660	300	0.98"	25	297	135	9.8"	250	59"	1500	259653	714.08
MLQ-600	1320	600	1.18"	30	600	270	13.7"	350	78"	2000	264904	1,172.38
MLQ-1000	2200	1000	1.57"	40	990	450	17.7"	450	98"	2500	264905	1,806.53
MLQ-2000	4400	2000	2.16"	55	1910	870	21.6"	550	118"	3000	264906	3,692.99
MLQ-3000	6600	3000	2.36"	60	2904	1320	25.60"	650	137"	3500	264908	5,753.17
MLQ-2000	4400	2000	2.16"	55	1910	870	21.6"	550	118"	3000	264906	3,692.9

2-Piece F.R.L. Units

These accessories improve air tool performance and increase tool life. F.R.L. units should be mounted as close to the tool as possible and regularly maintained for maximum efficiency. Lubricators have a ten position 0 to 9 dial for precise setting and resetting for various sizes of tools.

Model No.	Air Inlet	Width	Length	A.C.T. No.	Price \$
BFC 200H	1/4" NPT	140mm	206mm	105813	89.25
BFC 300H	3/8" NPT	140mm	206mm	105812	89.25
CFC 400H	1/2" NPT	176mm	250mm	126095	136.00






Coil Hose

This Polyurethane hose does not split or kink, two of the most common problems with nylon air hose. Its tight compact coils allow it to be stored out of the way on a busy workbench. Working length is 80% of overall length.

Model No.	;	Size		Straight Ends		N.P.T. Fittings		Price
Model No.	ID	Length	Α	В	Α	В	No.	\$
WPC-2510BAD	1/4"	10'	4"	20"	1/4" MR	1/4" MS	90203	10.83
WPC-2515BAD	1/4"	15'	4"	20"	1/4" MR	1/4" MS	90204	13.26
WPC-2525BAD	1/4"	25'	4"	20"	1/4" MR	1/4" MS	71023	17.55
WPC-3815BBE	3/8"	15'	4"	20"	3/8" MR	3/8" MS	66663	19.30
WPC-3825DBE	3/8"	25'	4"	30"	3/8" MR	3/8" MS	73296	27.21



MR-Male Rigid MS-Male Swivel



"Swivel Mate" Air Hose Connectors \$12.75 Model No. CT381R A.C.T. No. 100411

Swivel Mate swivels 360° at two points, allowing the air hose to drop straight to the floor regardless of how the tool is held.

Type: AluminumThread: 1/4 NPT





Air Motor Oil

WESPRO air motor oil is formulated with today's air tools in mind. It is lightweight and contains special detergents which clean the interior of the air tool while providing excellent lubricity. Emulsifying agents in the oil absorb moisture in the tool and carry it through to the exhaust.

Model No.	Size	A.C.T. No.	Price \$
AMO-005	1/2 Litre	91176	7.17
AMO-010	1 Litre	91177	10.24
AMO-040	4 Litres	91178	34.43
AMO-200	20 Litres	91179	148.35



Mini Manual Grease Gun Model No. GG02

\$14.46

A.C.T. No. 55007

Miniature sized hand grease gun with a special tip to apply grease in flush type fittings on air tool gear heads or bearing sections.

• Length: 6" (152 mm)





In-Line Oilers

Heavy duty in-line lubricators to be installed in air lines within 10-15 feet of tool. Rugged construction will allow dragging on the floor or ground. Designed for use with tools being used too far from the main air lines or wall mounted FRL units.

Model No.	Capacity	Thread	A.C.T. No.	Price \$
LO1000	473ml	1	90842	118.26
LO750	109ml	3/4	90841	84.47
LO500B	41ml	1/2	90840	72.46





Inline Oiler - Compact

Mini refillable inline oilers ensure air tools perform more reliably - Only 2" OAL!

Model No.	Туре	Capacity	Thread	A.C.T. No.	Price \$
MO250A	Aluminum	5ml	1/4NPT	85453	13.70
MO250B	Brass	5ml	1/4NPT	85454	7.65





Extreme Pressure Grease

Extreme pressure grease for air & electric power tool gearing and bearings.

Model No.	Size	A.C.T. No.	Price \$
EP1.5	400 Gram Tube	173793	15.30
EPG2/1.5	2 lb Tub	163533	27.47

Cordless Drill & Driver Kit Model No. EY7450LR2S

A.C.T. NO. 265579

3m Tough



- High capacity 3.3 Ah Li-ion battery
- Compact size (LxHxW): 8-9/16" x 9-3/4" x 2-1/2"
- Light weight (incl. battery): 4.70 lbs.
- High power: 505 in.lbs.
- Variable speed/reversible:
 - Low: 50-430 rpm - High: 160-1, 650rpm
- Clutch Torque (Approx.): 8.8-61.0 in.lbs. (3.0 in.lbs. per stage, total 18 stage)
- 1/2" Heavy duty keyless chuck
- · Charging Time (using EY0L81B charger)*:
 - Usable: 50 minutes - Full: 65 minutes

- · Electric brake
- LED work light
- Kit includes extra battery pack
- Max. Drill Diameter:
 - Wood: dia. 1-7/16"
 - Metal: dia. 1/2"
- · Max. Screws Driving:
 - Wood screw: dia. 5/16"
 - Self-drilling screw: dia. 1/4"
- Typical Applications:
 - General construction
 - Plumbing
 - Finishing carpentry
 - Electric installation work

Panasonic



While auantities last!

Cordless Impact Driver Kit

Model No. EY7550LR2S

\$295.00

A.C.T. NO. 265629

h TOUGH

18V

- High capacity 3.3 Ah Li-ion battery
- Compact size (LxHxW): 5-5/8" x 9-17/32" x 2-13/32"
- · Light weight (incl. battery): 3.53 lbs.
- High power: 1,370 in.lbs.
- · Variable speed/reversible
- · Brushless motor and hybrid switch
- 3 Speeds (High/Medium/Low)
- 1/4" Hex quick connect chuck
- · Charging Time (using EY0L81B charger)*:

Usable: 50 minutes Full: 65 minutes

- · Electric brake
- · LED work light
- · Belt hook
- Kit includes extra battery pack
- · Typical Applications:
 - Air conditioning installation
 - Automotive repair and maintenance
 - Assemble and disassemble scaffolding
 - Long wood screw/lag screw fastening

	High/Hard Mode	Medium Mode	Low/Soft Mode
Max. Torque	1,370 in.lbs.**	1,150 in.lbs.**	355 in.lbs.***
Speed at No Load	0-2,500 rpm	0-1,400 rpm	0-1,000 rpm
Impact/min.	0-3,300 ipm	0-2,800 ipm	0-2,000 ipm

Panasonic



While auantities last!

*Charging times are approximate

^{**}M14 High tensile bolt tightening for 3 sec.

^{***}M10 High tensile bolt tightening for 3 sec.



A.C.T. Blade Aide Sawing Coolant

A.C.T. BLADE AIDE is a full synthetic cutting fluid concentrate for bandsaw blades. Manufactured in Canada by Oemeta, A.C.T. BLADE AIDE is designed to be used when cutting both ferrous and non ferrous metals.

Model No.	Size	A.C.T. No.	Price \$
Blade Aide 4*	4L	225429*	27.29
Blade Aide 4*	4 x 4L	225429*	98.24
Blade Aide 20	20L	225430	102.06
Blade Aide 205	205L	225431	867.56

*Note: Please specify individual or case of 4 when placing order.

NOVAMET 100

- · For all metal machining applications
- Particularly recommended for aluminium and aluminium alloys chipping
- Longer sump life due to its high micro-biological stability
- Its high washing and flushing power ensures cleaner machines and work pieces
- Low foaming even with water hardness from 5°
- · Excellent protection against corrosion

Model No.	Size	A.C.T. No.	Price \$
40.870.24 PAIL	20kg Pail	234503	140.53
40.870.24 DRUM	200kg Drum	235495	1,331.67

NOVAMET 872

- High lubricity for light, medium and severe applications
- Robust biostability; low consumption combined with high wash activity
- Excellent corrosion protection
- Excellent foam behavior
- · Extended sump life
- Most advanced formulation without chlorine based additives

Model No.	Size	A.C.T. No.	Price \$
40.870.23 PAIL	20kg Pail	219464	131.99
40.870.23 DRUM	190ka Drum	219465	1.203.24



NOVAMET 900

- Excellent material compatibility on steel, yellow metals, aluminum alloys and magnesium
- Robust biostability; low consumption combined with high wash activity
- Excellent corrosion protection, foam behavior, and sump life
- Most advanced formulation without chlorine, sulphur or phosphorus based additives. Boron free.

Model No.	Size	A.C.T. No.	Price \$
42.875.13 PAIL	20kg Pail	219462	158.69
40.878.00 DRUM	200kg Drum	219463	1,481.32



BUYANY DRUM OF OEMETA PRODUCT FROM THIS PAGE AND GET THE NIMATIC OIL SKIMMER 2430 FOR 50% OFF! \$209.10 EACH


UNIMET AS260

- Robust biostability; low consumption combined with high wash activity
- Excellent corrosion protection
- · Excellent foam behavior
- Extended sump life
- Excellent machining performance with ferrous and yellow metals
- Most advanced formulation without chlorine, sulphur or phosphorus based additives

Model No.	Size	A.C.T. No.	Price \$
42.241.13 PAIL	20kg Pail	219466	115.22
42.241.13 DRUM	200kg Drum	219467	1,086.17

Cleaner EC

- · Alkalescent Cleaner
- · Easy handling; low foaming
- Good corrosion protection due to special inhibitors
- Compatible with emulsions and solutions, with no negative influence on the coolant
- Free of phosphate and bio-degradable



HYTAP Tapping Fluid

- High lubrication effectively prevents tool wear
- High viscosity simplifies the manual application to tool or work piece
- Self-emulsifying, easy-to-clean parts with aqueous media; no coolant contamination



Model No.	Size	A.C.T. No.	Price \$
42.710.19-1	1/2 litre	219470	10.44
42.710.19-2	Litre	219471	16.22
42.710.19-3	4 lit Jug	266234	53.65
42.710.19-4	18kg Pail	220232	182.53

BUY 3 GET 1 FREE

OSG's MMTS Promotion

SAME PART NUMBER

. Buy 3 of any one part number and receive 1 OSG tool of the same part number FREE


MIX AND MATCH

. Buy any 3 part numbers and receive 1 OSG tool FREE (with a diameter equal to or less than the smallest diameter purchased)

EXOPRO XPF Lists: 16050 (Inch/Coolant), 16150 (Metric/Coolant), 16250 (Inch), 16350 (Metric)

The EXOPRO® XPF & S-XPF taps represent a new evolution in forming tap technology. These form taps generate up to 50% less torque versus other forming taps, making it feasible to tap materials up to 40 HRC and with diamters up to or exceeding 1" in diameter.

- 1 Fluteless Forming Tap
- 2 40-50% Less Machining Torque
- 3 Coolant-Fed Version Available
- DIN Overall Length



EXOTAP* A-TAP* Lists: 16500 (Metric/Sp. Flute), 16505 (Inch/Sp. Flute), 16510 (Metric/Sp. Point), 16515 (Inch/Sp. Point)

The EXOTAP® A-TAP® is an all-purpose tap series designed to simplify tool management and to excel in a wide variety of materials and applications. The spiral flute series has unique geometry that enables greater chip control that can help produce tightly compacted chips for easy ejection from

- Sharp Cutting Edge Stabilizes Chip Shape
- Variable Lead Flute (PAT.) Accelerates Chip Evacuation
- OSG's Proprietary V Coating Promotes Long Tool Life
- Powder Metallurgy HSS High Wear Resistance



EXOCARB® WDO Lists: 5500 (3D), 5510 (5D), 5520 (8D), 5530 (10D), 5540 (20D), 5550 (30D/Coolant),

The EXOCARB® WDO utilizes OSG's WD1 coating that inhibits the wear on the shoulders and margin of the drill. Wear resistance is enhanced through improved hardness. Greater sharpness and longer tool life achieved through the new "wavy" point form.


- Wavy Point Form Greater Sharpness and Longer Tool Life
- WD1 Coating Increeses Wear Resistance
- Stable Low Thrust & Torque Low Energy Use
- Wide Variety of Sizes



EXOCARB® WD Lists: 5400 (20), 5410 (4D/No Coolant)

The EXOCARB® WD dnil series is OSG's premium line of solid carbide high performance drills. New wavy point edge form creates sharp cutting action for reduce thrust forces, while our proprietary WD1 coating provides drastically higher hardness and heat resistance, enabling higher drilling speeds and incredible tool life.

- Wavy Point Form
 Greater Sharpness and Longer Tool Life
- WD1 Coating Increases Wear Resistance
- Ultra-fine Micrograin Carbide Promotes Long Tool Life
- Sharp Cutting Edge Reduced Thrust and Torque





WD-40

WD-40 not only lubricates, it also cleans and protects metal parts. It effectively penetrates to loosen rusted parts and sticky mechanisms. It also works well to drive moisture from undesired locations. Available in 4L containers or in a convenient aerosol spray can.

342 g BONUS CAN 10% MORE!

Size	A.C.T. No.	Price \$
342 g (12 oz)	209098	7.70
3.78L	105876	35.60

Starrett[®]



M1 Industrial All-Purpose Lubricant

This superior lubricant produces a micro-thin, air-tight coating that simultaneously dries as it protects, avoiding dirt, grime, etc., that other "wet" lubricants actually attract. The can will spray upside down in awkward places without losing propellant power.

Description	A.C.T. No.	Price \$
12 oz Aerosol Can	140547	6.24
1 gal. Can (3.75L)	128073	39.15

BAHCO



Hacksaw Blades

Virtually unbreakable blades that can withstand high feed pressure to ensure fast and accurate cuts.

Model No.	Size	TPI	Pkg Qty	A.C.T. No.	Price \$/ea. When Buying Box Quantity
860110	12" x 1/2" x .025"	18	10/Pkg	172462	1.25
860120	12" x 1/2" x .025"	24	10/Pkg	53263	1.25
860130	12" x 1/2" x .025"	32	10/Pkg	172468	1.25





Huntington Wheel Dressers

These dressers will fulfill most general dressing needs where fast dressing is the primary requirement. Can be used for dressing which cleans away foreign particles and exposes sharp new cutting edges or for truing to restore the proper shape of the wheel. Choose Desmond Cutters for continued quality performance of your Huntington Dressers.

For Wheels	A.C.T. No.	Price \$
Under 10"	52590	18.70
	52595	2.49
10"-16"	52592	23.47
	52596	3.80
16" to 36"	52594	33.36
	79392	8.61
16" to 30"	65001	100.57
	61842	22.00
	Under 10" 10"-16" 16" to 36"	Under 10" 52590 52595 10"-16" 52592 52596 16" to 36" 52594 79392 16" to 30" 65001







Quicker Service with FastTrack by A.C.T. and Norton!

When you need belts fast, the right source to turn to is the best source. And, we are changing to serve you better. With our extensive stock offering and this simplified program, you can count on Norton belts to meet maximum performance needs or simply a competitive price.

Narrow Belts

Width*	Grit Size	Min. Order Qty	Case Qty	Max. Order Qty (Equals 2 Cases)
1/2" through 1"	All	50	200	400
Over 1" through 5"	All	10	50	100
Over 5" through 9"	All	10	20	40
Over 9" through 14"	All	10	10	20

^{*}FastTrack belt service applies to belts 25" and greater in length - with standard flexes and joints.



Tier	Cap Code	Size	Abrasive Grain	Grit	Backing	Applications
Good	CNAO	1/2"-14" Wide	Premium A/O	24-80 100-400	Y-wt. Polyester X-wt. Polyester	Heat-treated aluminum oxide grain and strong polyester backing for ferrous and nonferrous materials
Better	CNNZ	1/2"-14" Wide	Zirconia Alumina	24-120	Y-wt. Polyester	Zirconia alumina grain, with grinding aid, for grinding heat-sensitive alloys: Inconel, titanium and stainless steel
Best	CNSG	1/2"-14" Wide	Ceramic Alumina	24-80, 120	Y-wt. Polyester	Ceramic grain with special grinding aid, designed for grinding hard- to-grind alloys and heat-sensitive jobs

									cturer part numbe	
	CNAO (Aluminum Oxide) Good CNNZ (Blue Norzon) Better								CNSG (Ceramic) Bes	1
Belt Size	Grit	Spec	Norton UPC# (Prefix 776960)	Price \$/ea	Spec	Norton UPC# (Prefix 776960)	Price \$/ea	Spec	Norton UPC# (Prefix 776960)	Price \$/ea
2 x 72	40	CNAO	70971	2.29	CNNZ	70577	3.57	CNSG	70414	4.44
2 x 72	60	CNAO	71921	1.96	CNNZ	70659	2.96	CNSG	70472	3.80
2 x 72	80	CNAO	71922	1.77	CNNZ	70660	2.57	CNSG	70473	3.37
2 x 72	120	CNAO	71980	1.68	CNNZ	70635	2.57	CNSG	70393	3.17
2 x 90	24	CNAO	70972	2.97	CNNZ	70578	4.96	CNSG	70474	5.35
2 x 90	36	CNAO	70973	2.84	CNNZ	70579	4.72	CNSG	70475	5.08
2 x 90	40	CNAO	70974	2.79	CNNZ	70580	4.41	CNSG	70415	4.47
2 x 90	60	CNAO	71923	2.51	CNNZ	70661	3.84	CNSG	70476	4.03
2 x 90	80	CNAO	71924	2.40	CNNZ	70662	3.55	CNSG	70477	3.76
2 x 90	120	CNAO	71988	2.31	CNNZ	70636	3.55	CNSG	70394	3.61
4 x 100	24	CNAO	71330	6.43	CNNZ	70606	10.71	CNSG	70443	11.55
4 x 100	36	CNAO	71331	6.12	CNNZ	70607	10.21	CNSG	70444	10.99
4 x 100	40	CNAO	71332	6.03	CNNZ	70608	9.55	CNSG	70445	9.67
4 x 100	60	CNAO	71948	5.41	CNNZ	70681	8.28	CNSG	70496	8.69
4 x 100	80	CNAO	71950	5.19	CNNZ	70682	7.63	CNSG	70497	8.11
4 x 132	24	CNAO	71333	7.95	CNNZ	70609	13.23	CNSG	70446	14.25
4 x 132	36	CNAO	71334	7.56	CNNZ	70610	12.61	CNSG	70447	13.57
4 x 132	40	CNAO	71335	7.44	CNNZ	70611	11.79	CNSG	70449	11.93
4 x 132	60	CNAO	71951	6.68	CNNZ	70683	10.24	CNSG	70498	10.73
4 x 132	80	CNAO	71953	6.39	CNNZ	70684	9.43	CNSG	40799	10.03
6 x 48	24	CNAO	71336	5.85	CNNZ	70612	9.55	CNSG	70450	12.63
6 x 48	36	CNAO	71337	5.57	CNNZ	70613	9.08	CNSG	70451	12.03
6 x 48	40	CNAO	71338	5.36	CNNZ	70614	8.33	CNSG	70452	10.37
6 x 48	60	CNAO	71954	4.59	CNNZ	70685	6.85	CNSG	70500	8.88
6 x 48	80	CNAO	71955	4.16	CNNZ	70686	6.00	CNSG	70501	7.87
6 x 89	24	CNAO	71345	8.87	CNNZ	70622	14.77	CNSG	70459	15.91
6 x 89	36	CNAO	71346	8.44	CNNZ	70623	14.07	CNSG	70460	15.16
6 x 89	40	CNAO	71347	8.31	CNNZ	70624	13.16	CNSG	70461	13.32
6 x 89	60	CNAO	71961	7.47	CNNZ	70691	11.41	CNSG	70506	11.99
6 x 89	80	CNAO	71962	7.15	CNNZ	70692	10.53	CNSG	70508	11.20
6 x 100	24	CNAO	71348	9.64	CNNZ	70625	16.05	CNSG	70462	17.31
6 x 100	36	CNAO	71349	9.19	CNNZ	70627	15.31	CNSG	70463	16.48
6 x 100	40	CNAO	71350	9.03	CNNZ	70628	14.31	CNSG	70464	14.5
6 x 100	60	CNAO	71963	8.11	CNNZ	70693	12.41	CNSG	70509	13.04
6 x 100	80	CNAO	71964	7.76	CNNZ	70694	11.45	CNSG	70510	12.17



Alkaline Batteries

Size	PKG QTY	A.C.T. No.	Price \$/Each When You Buy Pkg Quantity
AAAA	6	196908	10.49/pkg
AAA	8	247442	0.78/ea.
AA	8	247441	0.58/ea.
С	6	247443	1.28/ea.
D	6	247444	1.38/ea.
9V	6	247440	2.33/ea.
6V Lantern Battery w/ Spring Terminals	1	247503	3.97/ea.



Tape Measures

- Durable high impact ABS case.
- Available with or without magnetic tip.

Non-Magnetic Tip

	•					
Model No.	Length	Width	Graduation	A.C.T. No.	Price \$	
TGTM-001	16'	3/4"	Imperial Only	274361	2.50	
TGTM-002	16'	3/4"	Imperial & Metric	274363	2.50	
TGTM-003	25'	1"	Imperial Only	274365	3.94	
TGTM-004	25'	1"	Imperial & Metric	274366	3.94	

Magnetic Tip

Model No.	Length	Width	Graduation	A.C.T. No.	Price \$
TGTM-005	16'	3/4"	Imperial Only	TGTM-005*	2.66
TGTM-006	16'	3/4"	Imperial & Metric	TGTM-006*	2.66
TGTM-007	25'	1"	Imperial Only	TGTM-007*	4.10
TGTM-008	25'	1"	Imperial & Metric	TGTM-008*	4.10

^{*}Manufacturer part number listed.



Carbide Point Scriber with Magnet

Overall length of 6". Tungsten carbide tip marks hard materials including hardened steel, ceramics and glass.

Model No.	A.C.T. No.	Price \$
88CM	59941	9.36
Replacement Tip	58093	3.79



Utility Knives

The original heavy-duty cutter. Contoured handle includes a ratchet wheel blade locking mechanism and an anti-slip rubber grip insert (L-2 only). Uses any OLFA heavy-duty replacement blade.

Model No.	A.C.T. No.	Price \$
L-1	85769	7.54
L-2	139610	9.00

Replacement Blades for Knife Models	Pkg Qty	A.C.T. No.	Price \$
L-1, L-2, NH-1, NH-AL	10	85770	5.61
L-1, L-2, NH-1, NH-AL	50	102466	21.90

Stringer Bead Weld Cleaning Brushes

Each knot is twisted through its own hole and locked into an individual sprocket. This prevents the knots from moving around the radius and allows them to have a stronger striking action on the work surface.

Dia.	Wire Type	Wire Size	Arbor Hole	Face Width	Trim Length	Max RPM	A.C.T. No.	Price \$
5"	Steel	.020	5/8-11NC	3/16"	7/8"	12,500	129738	13.23
5"	Stainless	.020	5/8-11NC	3/16"	7/8"	12,500	136293	26.69
6"	Steel	.020	5/8-11NC	3/16"	1.1/8"	12,500	177601	19.52
6"	Stainless	.020	5/8-11NC	3/16"	1.1/8"	12,500	141311	35.05
6.1/2"	Steel	.023	5/8-11NC	1/2"	1.3/8"	12,500	127226	17.51
6.7/8"	Steel	.020	5/8-11NC	3/16"	1.1/8"	9,000	128879	19.91
6.7/8"	Stainless	.020	5/8-11NC	3/16"	1.1/8"	9,000	141123	34.81





Knot Cup Brushes - Steel

Excellent for cleaning prior to welding. Great for removing rust and paint.

Dia.	Wire Type	Wire Size	Arbor Hole	Trim Length	Max RPM	A.C.T. No.	Price \$
5"	Steel	.023	5/8-11NC	1.3/8"	7,000	94844	34.94
6"	Steel	.023	5/8-11NC	1.3/8"	6,600	130230	44.47
6"	Stainless	.023	5/8-11NC	1.3/8"	6,600	157959	85.46



Picquic SIXPAC Plus

The original Picquic - Full size for professional or at home use. Solid handle for maximum comfort and torque; no moving parts to break (or lose). Anodized aluminum alloy shank for years of use. Bits are ideal for use in drills and powerdrivers.

3" length, 1/4" Hex Powerbits



Model No.	Colours	Packaging	Ctn/MC	A.C.T. No.	Price \$
88001B	Black	Bulk Display	12/120	112519	13.04

PICOVIC



Picquic Stubby

The World's first-ever Multiple bit Stubby and still considered the best! Ideal for the kitchen drawer and superb for close-quarters work. High-strength magnet holds 'working' bit and screw securely. 1/4" hex 1.3" insert bits are ideal for powerdriving.

1.3" length, 1/4" Hex insert bits



Model No.	Colours	Packaging	Ctn/MC	A.C.T. No.	Price \$
91002B	Black	Cookie Jar	12/120	112520	10.44

Picavic





Riggers Split-Leather Gloves

Model No. TGG-416-L

A.C.T. No. 234701

- Split Leather Fitter Glove
- Patch Palm
- Type: Econo



The Prospect Welders Gloves

- · Split cowhide leather
- · Cotton jersey shell, flame resistant heavy duty rubber on knuckle bar
- · Reinforced welted seams
- Wing thumb
- · Stitched with Kevlar® thread gauntlet style cuff

Style	п	A.C.T. No		Price \$/Pair
Style	" м	L	XL	Filce \$/Faii
2711	279357	279359	279360	6.60



Touch 'n Tuff Nitrile Gloves

- Made of 100% thin-mil nitrile
- · Lightweight and comfortable to wear

Type		A.C.1	Г. No.		Price
Type	S	M	L	XL	\$/Box
TGG-110	283313	283315	283316	283317	7.39

Packaged 100 gloves per box.



Disposable Coveralls

- White microporous SF material
- · Lightweight and breathable
- · Zipper front, attached hood, elastic wrists, ankles, and waist.

Model No.	Size	Material	Packaging	A.C.T. No.	Price \$/Box
TGDC50-L	L	50 GSM	25/box	285650	64.67
TGDC50-XL	XL	50 GSM	25/box	285651	67.33
TGDC50-2XL	XXL	50 GSM	25/box	285652	68.00



Fast Orange Hand Cleaner

Fast Orange is the #1 selling biodegradable, waterless, petroleum solvent-free hand cleaner. It contains no harsh chemicals, mineral oils or ammonia that can sting cuts and abrasions. Pure, fresh-smelling natural citrus power does the cleaning while aloe, lanolin, glycerin and jojoba condition and protect skin. Fast Orange gently deep cleans the toughest soils. Works great on laundry stains, scuff marks, tile floors, pet odors and many other household cleaning needs.

While quantities last!

Model No.	Description	Packaging	A.C.T. No.	Price \$
20061	20861 Fast Orange® Pumice Lotion 3.78L Bottle	Individual	187697	17.74
20001		4/Case	10/09/	16.32

Note: Please specify individual or case of 4 when placing order.

Transfer Punch Sets

Model No. 200-750

Α.C.T. No. 113986

- · 28 Punches in Metal Indexed Stand
- · Heat-treated tempered steel
- Consists of one each of punch sizes 3/32 thru 1/2 x 64th plus 17/32 in metal indexed stand



8pc Pin Punch Set

Model No. 606-630

\$40.16

A.C.T. No. 211499

These round shank pin punches have clean and well cut knurling which provides positive, non slip grip. This range of punches have a black oxide finish.

Sizes: 1/16, 3/32, 1/8, 5/32, 3/16, 1/4, 5/16, 3/8



Long Drive Pin Punches

Model No. 283975

\$19.95

A C T No. 286156

- · Tool steel with black oxide finish and hardened on both ends
- Length: 8" (drive pin section: 3-1/2")
- Point sizes: 1/8", 3/6", 1/4", 5/16", and 3/8"
- Supplied in storage case



Drive Pin Punches

Model No. 283976

\$17.09

A.C.T. No. 283976*

- · Tool steel with black oxide finish and hardened on both ends
- · Length: 4"
- Point sizes: 1/16", 3/32", 1/8", 5/32", 3/16", 7/32", 1/4", and 5/16"
- · Supplied in storage case
- *Manufacturer part number listed.



Jobber Drill Sets - Shank with 3 Flats

240-AQF Drill Sets – These heavy-duty 135° Split Point drills are the same as the 240-UB with three flats on the shank to give positive chuck grip, (3/16" and larger). These drills are ideal for use with hand held drills and keyless chucks.

▲ 240-AQF

Model No.	Description	A.C.T. No.	Price \$
AQF-13	13pc Set (1/16" - 1/4" by 1/64" increments)	220150	22.46
AQF-21	21pc Set (1/16" - 3/8" by 1/64" increments)	220151	54.99
AQF-29	29pc Set (1/16" - 1/2" by 1/64" increments)	220139	109.98



Mechanics Bench Vise

Record vises are among the most popular and widely used general-purpose vises for light to medium duty applications.

Model No.	Jaw Width	Jaw Opening	Jaw Depth	A.C.T. No.	Price \$
3B	4"	4.3/4"	2.3/4"	60475	89.01
5B	5"	6.1/2"	3.1/4"	65601	153.79
6B	6"	8"	3.1/2"	60027	189.72
8B	8"	9.1/4"	4"	100355	225.85



Floor-Dry Absorbent

Floor-Dry Premium Oil Absorbent is made of 100% Diatomaceous Earth (DE) and is an all-purpose absorbent designed for the quick clean up of water, oil and grease. Made from Diatomaceous Earth, a naturally occurring mineral with superior absorptive ability, this high quality product delivers 50% more absorbency per pound than clay alternatives.

Benefits:

- · Provides more absorption for the money
- · Easy to use and transport
- · Environmentally friendly
- 100% Natural mineral
- Granulation-Coarse

F.O.B. A.C.T. Burnaby

A.C.T. No.	Quantity	Price	
	1 to 14 bags	11.40 ea.	
267679	15 to 39 bags	10.04 ea.	
	40+	9.50 ea.	





OIL SPILLS Pour over oil spills on concrete driveways and garage floors. Sweep up with broom



GARAGES Use OptiSorb® for spills on



INDUSTRIAL CHEMICALS Excellent multi-purpose absorbent for a wide variety of industries.



MRO APPLICATION Excellent multi-purpose absorbent for a wide variety of industries.



CONTROLLING ODOR Cover bottom of garbage can to absorb moisture



CATLITTER Excellent for use as cat litter



Our credit terms are Net 30 days for those customers who have an open account. To assist those customers who have no account established thus far, we accept VISA, MASTERCARD and INTERAC Direct Payment. Application for credit is available upon request.

PRICES

Prices are subject to change without notice. Some prices subject to stock availability. All taxes (GST & PST) will be extra where applicable. Items may not be exactly as shown.

DELIVERY

Prices are F.O.B. your nearest A.C.T. warehouse unless otherwise stated.

Shipping will be prepaid on all orders that are both over \$250 Net and under 50 lbs in weight. (Excluding hazardous and prohibited goods.) Overnight Air shipping also available to most major centers, please inquire.

FASTEST SERVICE

To ensure the fastest service, telephone, fax or E-mail your order to the nearest participating A.C.T. Branch.

A.C.T. EQUIPMENT SALES LTD. www.actequipment.com

Burnaby Branch 4455 Alaska Street Burnaby, BC V5C 5T3 Tel: (604) 294-6271 Fax: (604) 294-8131 1(800) 667-1504

burnaby@actequipment.com

Edmonton Branch 6786-75th St. N.W. Edmonton, AB T6E 6T9 Tel: (780) 462-1777 Fax: (780) 461-5605 1(800)661-5979 edmonton@actequipment.com

Calgary Branch Bay 10, 7003-30th St. S.E. Calgary, ABT2C 1N6 Tel: (403) 279-6016 Fax: (403) 279-5390 1(800) 685-8155 calgary@actequipment.com

Saskatoon Branch Unit 112 - 4002 Arthur Rose Ave. Saskatoon, SK S7P 0C9

Tel: (306) 244-4810 Fax: (306) 244-4811 1(866) 234-0120

saskatoon@actequipment.com

Winnipeg, MB R2R 0J1 Tel: (204) 783-3210 Fax: (204) 783-3224 1(877) 783-3201 winnipeg@actequipment.com

Winnipeg Branch

Unit 4 - 2065 Logan Ave.

